

FICHA TÉCNICA

DISEÑO PIEDRA TECNOLÓGICA

MODELO / MODEL		ALLISON SERIES		
FOTO / PICTURE		 <p>P.E. ALLISON BLANCO SATINADO 60X120 RECT. P.E. ALLISON CREMA SATINADO 60X120 RECT. P.E. ALLISON GRIS SATINADO 60X120 RECT. P.E. ALLISON PERLA SATINADO 60X120 RECT.</p>		
FORMATO / SIZE		60 X 120 X 1 CM. RECTIFICADO		
GRUPO / GROUP		Bla		
TIPO / TYPE		PORCELANICO SATINADO / Glazed Porcelain Tile		
ALLISON BLANCO: 25 CARAS PERLA: 17 CARAS GRIS: 17 CARAS CREMA: 11 CARAS				
DESCRIPCION DEL TEST / TEST DESCRIPTION		VALOR DEL TEST / TEST VALUE	SELEKTIA Porcelanato	NORMA / STANDARD
ABSORCIÓN DE AGUA / WATER ABSORPTION		AA < 0,5%	Cumple / Passed	UNE-EN-ISO 10545-3
FUERZA DE ROTURA / BREAKING STRENGTH		> 1300 N	Cumple / Passed	UNE-EN-ISO 10545-4
RESISTENCIA A LA FLEXIÓN / RESISTANCE OF FLEXION		> 35 N/mm ²	Cumple / Passed	UNE-EN-ISO 10545-4
ABRASION SUPERFICIAL / SURFACE ABRASION		Clase / Class	PEI IV (GRIS PEI III)	UNE-EN-ISO 10545-7
RESISTENCIA AL CUARTEO / CRACKING RESISTANCE		Requerido / Requested	Cumple / Passed	UNE-EN-ISO 10545-11
RESISTENCIA A LA HELADA / FROST RESISTANCE		Requerido / Requested	Cumple / Passed	UNE-EN-ISO 10545-12
RESISTENCIA QUIMICA / CHEMICAL RESISTANCE	(PRODUCTOS DOMESTICOS Y DE PISCINA / Domestic & Swimming Pool Products)	Mínimo / Minimum GB	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LOS ACIDOS / ACID RESISTANCE		GHA	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LAS BASES / ALKALINE RESISTANCE		GHA	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LAS MANCHAS / RESISTANCE TO STAINS		Mínimo / Minimum Class 3	Cumple / Passed	UNE-EN-ISO 10545-14
RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE		Metodo Disponible / Available Method	Class 1	UNE-ENV 41901:2017 EX
RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE		D.C.O.F.	0.30	ANSI A137. 1:2012. 9.6
RESISTENCIA AL RAYADO / HARDNESS (MOHS)		Mínimo / Minimum 3	Cumple / Passed	EN 101